Ultrasound Bath For Strainer With 200W Heating Power 2.85 Gallon

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Skymen
- Certification: CE ROHS FCC SGS
- Model Number: JP-040S
- Minimum Order Quantity: 1 unit
- Price: Negotiation
- Packaging Details: 1unit per box
- Delivery Time: In Stock
- Supply Ability: 8000 pcs per month

Product Specification

- Model: JP-040S
- Frequency: 40KHz
- Capacity: 2.85 Gallon
- Tank Size: 12*9*6 Inch
- Ultrasonic Power: 120W/240W
- Heating Power: 200W
- Material: SUS 304
- G.W: 8.4KG
- Highlight: **30min Timer Ultrasonic Parts Cleaners, Bench Top Ultrasonic Cleaner SUS304, SUS304 Ultrasonic Cleaning Equipment**

More Images

for more products please visit us on skymenultrasonic.com

Our Product Introduction

for more products please visit us on skymenultrasonic.com

Product Description

Embroidered Eyebrow Pencil Ultrasound Bath In Beauty Salon With 200W Heating Power 2.85 Gallon
Skymen ultrasonic cleaner is professional for diamond jewelry, glasses, watches, dentures, bolt carrier groups, air craft, auto gun parts, Vinyl record, dental equipment, tattoo, glass pipes, bicycle parts, scuba equipment, carbs, vinyl albums, golf balls, firearms, handguns, pistol, revolvers and reloading dies, clocks, dental instruments, door hardware, lawn mowers, pressure cleaners, motorcycles, older vehicles, hooks and brass, gas air compressors, gear, tools, engine carburetors, cartridge cases, brass bullet casings, clock movements, clippers, golf clubs, steel machine parts, cycle carb jets, hardware, handgun, cartridge cases, rifle, nuts, bolts, oily, gunky tools, brass shells, engine parts, fruits, vegetables, car Injector.

Model	**JP-040S**
Ultrasonic Frequency	40KHz
Transducer Quantity	4pcs
Ultrasonic Power	240W/120W
Heating Power	200W
Tank Capacity	10.8L/2.85Gallon
Tank Size	300*240*150mm
Machine size	380*290*280mm
Packing size	440*365*360mm
Net weight	7.6KG
Gross weight	8.6KG
Time Range	1~30 minutes
Temperature Range	Room temperature~80 /176
Tank material	SUS 304
Tank thickness	1mm
Shell material	SUS 201
Shell thickness	0.8mm
Slope panel degree	20°
Drain Valve	✓
General switch	✓
Degas	✓
Semi-wave	✓
Lid	✓
Basket	✓
Voltage	110V; 220V
Plug	European Plug; US plug; Austrslian Plug; British Plu
Detergent suggestion	No stronger acid or alkali
OEM	Yes
OEM MOQ	50pcs
Origin	Guangdong China
Business category	Manufacturer
Lead time	7 days after payment if order quantity is below 20pcs
Payment term	By cash; by credit card; by Paypal
Warranty	1 year

Stainless Bench Top

Model	Capacity	Tank Size	Ultrasonic Power	Heating Power	Frequency	Tank thickness	Material
	(L)	(L*W*H)mm	(W)	(W)	(KHz)	(mm)	SUS304
JP-008	0.8	150*85*65	35	0	40	1	SUS304
JP-009	0.9	150*135*65	60	100	40	1	SUS304
JP-010T	2	150*165*100	60	100	40	1	SUS304
JP-020S	3.2	240*135*100	120	100	40	1	SUS304
JP-030S	4.5	300*150*100	180	200	40	1	SUS304
JP-031S	6.5	300*150*150	180	200	40	1	SUS304
JP-040S	10	300*240*150	240	200	40	1	SUS304
JP-060S	15	330*300*150	360	300	40	1	SUS304
JP-080S	22	500*300*150	480	500	40	1	SUS304
JP-100S	30	500*300*200	600	500	40	1	SUS304

Product Show:


HEATING SYSTEM
Built-in heating board,You can adjust the heating water temperature from 20 to 80°C. It's efficient to remove oil and wax
Heating board

Product details

1.

Printed surface stainless steel

fingerprint and dirt resisting

2.

SUS304 inner tank

non-welded stamped tank features corrosion and heat resisting

3.

Heat emission design

heat emission holes at the bottom increase working life



4.

Drain valve

The drain vavle is made of high quality copper, corrosion-resistant and switch adjustable

JP-040S 10L Product Show

Heating power	Ultrasonic power	Transducer
200W	240W	4 Pcs

PAY ATTENTION ON DETAILS

01

Insulated handle design

Anti-static and anti-high temperature, more secure

02

Stainless steel drain valve

One-half inch large drain valve, quicker to drain

03

Cooling vents

Fast heat dissipation, protecting the circuit board and enhancing the service life

04

Heat - resistant power cord

One-half inch large drain valve, quicker to drain

05



Non-slip anti-shock pad

Non-slip, safer

06

Safety switch

With ground insurance switch

07

Stainless steel cleaning basket

Fine workmanship and durability





Application Area:

MULTIPURPOSE CLEANING

It's efficient for most of household items that could be used to clean. get the best cleaning effects with the least effort.

Glasses


Watchband

Jewelry

Tableware

Toothbrush

Denture

Shaver

Bottles&nipples

Nail Tools

Before

After

Before

After

Before

After

Before

After

COMPARISON OF CLEANING EFFECT

Before

After

Before

After

Before

After

Before

After


Suitable for varieties of palces
Factory
Labs
Hardware store

Before
After

Before
After

Before
After

PRODUCT FEATURES

1. mechanical timing:
The working time adjustable from 0-30 minutes or normal open mode.

2. mechanical control:
mechanical control heater, 20-80 adjustable,temperature error within +-2

3. high quality bath:
High qualtiy SUS 304 stainless steel punch forming bath with noise proof

4. anti-skid treatment:
the machine is steady with the non-slip,shock-proof,anti-static,pressure-proof mats at the bottom

5. ceramic heater:
New ceramic heater is stable and efficient

6. Humanized design,remarkable cleaning effect:
Tank capactity over 6L with the drain vavle; high cleaning efficiency, no harm to surface

Industrial Ultrasonic Cleaning Machine

Model	Capacity	Tank Size	Transducers	Ultrasonic Power	Heating Power	Tank thickness	Frequency
	(L)	(L*W*H)mm	(pcs)	(W)	(W)	(mm)	(KHz)
JP-120ST	38	500X300X250	12	600	1500	2	28/40
JP-180ST	53	500X350X300	18	900	1500	2	28/40
JP-240ST	77	550X400X350	24	120	3000	2	28/40
JP-300ST	99	550X450X400	30	1500	3000	2	28/40
JP-301ST	99	800X300X400	30	1500	3000	2	28/40
JP-360ST	135	600X500X450	36	1800	4500	2	28/40
JP-480ST	175	700X500X500	48	2400	6000	2	28/40
JP-600ST	264	800X600X550	60	3000	6000	2	28/40
JP-720ST	360	1000X600X600	72	3600	9000	2	28/40
JP-1108ST	540	1000X900X600	108	5400	18000	2	28/40
JP-1144ST	960	1200X1000X800	144	7200	27000	2	28/40

Immersible Transducer Plate Image:



Model	Plate Size	Transducers	Ultrasonic Power	Generator	Suitable tank
	(L*W*H)mm	(pcs)	(W)	(set)	(L)
JP-1006I	305*205*100	6	300	1	10~15
JP-1012I	355*305*100	12	600	1	30~40
JP-1018I	340*280*100	18	900	1	60~70
JP-1024I	430*280*100	24	1200	1	70~80
JP-1030I	460*370*100	30	1500	1	90~100
JP-1036I	550*450*100	36	1800	1	130~140
JP-1048I	600*450*100	48	2400	2	170~180

Immersible Transducer Tube

Image:

1.5

Model	Tube Size	Transducers	Ultrasonic Power	Generator	Length of wire
	(D*H)mm	(pcs)	(W)	(set)	(M)
JM-1003	57*180	3	150	1	1.5
JM-1006	57*300	6	300	1	1.5
JM-1012	57*550	12	600	1	1.5
JM-1018	57*750	18	900	1	1.5
JM-1024	57*1000	24	1200	1	1.5
JM-1036	57*1520	36	1800	1	

Immersible Transducer Plate/tube can be put in any tank, but it doesn't have heating function.

The price of tube is much higher than plate, Ultrasonic Tube is only used for special purpose, such as in Lab.

Skymen Technology Corporation Limited

86-755-27094405 info@skymen.cc skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen