



4.5L 300W Ultrasonic Instrument Cleaner FCC For Stainless Steel Blade

Our Product Introduction

for more products please visit us on skymenultrasonic.com

Basic Information

- Place of Origin: China
- Brand Name: Skymen
- Certification: CE, ROHS, FCC
- Model Number: JP-030PLUS
- Minimum Order Quantity: 1 unit
- Price: Negotiation
- Packaging Details: Foam carton
- Delivery Time: In Stock



Product Specification

- Tank Volume: 4.5L
- Inner Tank Size: 11.8x5.9x3.9"
- Machine Dimension: 13x7.8x9.3"
- Gross Weight: 5.4KG
- Ultrasonic Power: 180/300W
- Heating Power: 200W
- Highlight: 300W Ultrasonic Instrument Cleaner, 4.5L Ultrasonic Instrument Cleaner, FCC Portable Ultrasonic Cleaner



More Images



Product Description

Ultrasonic Bath for Stainless Steel Blade With CE 300W Stronger Power Ultrasonic Cleaner

Safe, easy-to-use ultrasonic cleaners from Grainger can be especially effective for cleaning metal and plastic machinery and parts. Choose the size, timing and heat options to fit specific cleaning tasks, such as removing blood, proteins and contaminants from glassware and lab instruments; eliminating dirt, grease, waxes and oils from switches and gears and cleaning flux and contaminants from electronics

Specifications:

Model No.	JP-030PLUS
Function	Ultrasonic cleaning + Hot water cleaning
Ultrasonic Frequency	40kHz
Tank Material	SUS 304
Tank Capacity	4.5 Liter
Inner tank dimension	300*150*100mm / 11.8x5.9x3.9" (Length*width*deep)
Machine dimension	330*200*235mm / 13x7.8x9.3"(Length*width*height)
Gross weight of machine	5.4KG; packed by foam in carton
Ultrasonic Power	180/300W
Heating Power	200W
Time setting of Ultrasonic	0~30 minutes
Temperature setting	Room temperature ~ 80°C / 176°F adjustable
Drain value	No
Lid	Yes
Basket	Yes
Power supply	220V, 110V
Warranty	1 Year, free spare parts within 1 year, online technical support
Certificate	CE; RoHS; FCC; REACH
Lead time	3 Working days
Shipping time	5~7 day by express




Same serie machine with different capacity:

Model	Capacity (L)	Tank Size (L*W*H)mm	Ultrasonic Power (W)	Heating Power (W)	Frequenc y (KHz)	Tank thickness (mm)	Material
JP-020PLUS	3.2	240*135*100	120/180	100	40	1	SUS304

JP-030PLUS	4.5	300*150*100	180/300	200	40	1	SUS304
JP-031PLUS	6.5	300*150*150	180/300	200	40	1	SUS304
JP-040PLUS	10	300*240*150	240/480	200	40	1	SUS304
JP-060PLUS	15	330*300*150	360/600	300	40	1	SUS304
JP-080PLUS	22	500*300*150	480/840	500	40	1	SUS304
JP-100PLUS	30	500*300*200	600/1080	500	40	1	SUS304

Cleaning effect show:

Before & After Cleaning Comparison



How to Maintain Your Ultrasonic Tool Cleaning Bath

As noted above, loose rust should be scraped or wire brushed before parts are cleaned.

Contaminants that rise to the surface should be skimmed off and disposed of properly.

When the cleaning effectiveness falls off drain the tank and dispose of the solution according to local regulations. Take this time to thoroughly clean the tank following the manufacturer's recommendations.

In summary, dirty or rusted tools and other metal parts such as pumps, gears, and mechanical equipment can often be restored in an ultrasonic cleaner.



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com

